

Identidade e Controlo de Acesso baseado em Claims na plataforma Windows Azure

Pedro Félix e David Júlio

Microsoft, Tagus Park, Oeiras

27 e 28 de Janeiro de 2011

Outline

- Day 1
 - The claims-based model and specifications
 - Windows Identity Foundation (WIF)
 - The Azure AppFabric Access Control Service
 - Building ASP.NET based identity consumers (web apps) using WIF
 - WIF and ASP.NET on Windows Azure
- Day 2
 - Building WCF based identity consumers (web services) using WIF
 - WIF and WCF on Windows Azure
 - Building identity providers (web apps and services) using WIF
 - Active Directory Federation Services 2 (ADFS 2)


Day 1

- **HOL 1 – ASP.NET web app with Google and Facebook based authentication, using Access Control Service**
- The claims based model, use cases and specifications
- The Windows Identity Foundation
- The Azure AppFabric Access Control Service (ACS)
- **HOL 2 – creating and configuring an ACS tenant**
- WIF and ASP.NET deep dive
- **HOL 3 – exploring WIF and ASP.NET**
- Brief intro to Windows Azure
- WIF and Windows Azure
- **HOL 4 – moving a claims based ASP.NET web app to Windows Azure**

Hands-On-Lab 1

- Create default ASP.NET project
- Create and configure IIS site with HTTPS support
- Check behavior
- “Add STS reference”
 - <https://demos-ciws.accesscontrol.appfabriclabs.com/FederationMetadata/2007-06/FederationMetadata.xml>
- Check behavior
- Minor “hacks”
- Check behavior
- Add code to show claims

HOL 1




CLAIMS BASED MODEL

The claims model - claims

- *Identity* as a set of claims
 - Google::alice4demos@gmail.com
 - Facebook::"Alice Demos"
 - ISEL::**student**
 - OrganizationA::**Employee**
 - ADSE::**Beneficiary**
 - PurchaseApp::**PurchaseManager**
- A *claim* is a declaration made by an entity
 - Entities: ISEL, OrganizationA, Google, Facebook
 - Claims: name, role, email, authorization
- Opposite to *Identity* as a *unique identifier*

The Claims Model - participants




Concrete components

- Claims
- Tokens
 - Claims packaging
 - Origin authentication
 - Confidentiality
 - Proof-of-possession
- Protocols
 - Token request and communication
- Policy and metadata
 - Requirements and capabilities description


Claims transformers

- Example: <https://demos-ciws.accesscontrol.appfabriclabs.com/>
- Bridge between
 - Technological boundaries
 - Protocols: E.g. OpenID protocol \leftrightarrow WS-Fed protocol
 - Token formats: SAML \leftrightarrow SWT
 - Organizational boundaries
 - E.g. Domain group \rightarrow Public Role
 - E.g. Public Role \rightarrow Authorization
- Claim inference – policy evaluation


Federation



Not only for Federation



Not only for Federation



SPECIFICATIONS


Specifications

- Protocols
 - WS-Federation
- Token formats
 - SAML (Security Assertion Markup Language)
- Metadata
 - SAML and WS-Federation metadata

WS-Federation

- OASIS specification
 - http://www.oasis-open.org/committees/tc_home.php?wg_abbrev=wsfed
- Defines
 - Metadata format
 - Protocol for passive scenarios (browser)
 - HTTP protocol usage
 - Message parameters
 - Active protocol is defined by WS-Trust
- Uses
 - Metadata format from SAML
 - Messages formats from WS-Trust

WS-Federation



WS-Federation

- Request parameters
 - **wa** = wsignin1.0 (action)
 - **wtrealm** = <https://www.rp.ciws:8443> (req. realm)
 - **wctx** = <opaque> (req. context)
 - **wct** = <date-time>
 - **wreply** = <return url>
 - **whr** = <home realm>
- Response parameters
 - **wa** = wsignin1.0
 - **wctx** = <opaque> (req. context)
 - **wresult** = < **RequestSecurityTokenResponse** XML elem.>

RequestSecurityTokenResponse

<RequestSecurityTokenResponse Context = “req. ctx”>

<Lifetime>

<Created> ...

<Expires> ...

<AppliesTo>

<EndpointReference>

<Address> https://www.rp.ciws:8443

<RequestedSecurityToken>

[SAML assertion, incl. signature]

<TokenType> urn:oasis:names:tc:SAML:2.0:assertion


<RequestType> Issue

<KeyType> NoProofKey


SAML Assertion

<Assertion ID = “...” IssueInstant = “...” Version = “2.0”>
 <Issuer> <https://demos-ciws.accesscontrol.appfabriclabs.com/>
 <Signature> **[XML DSIG signature, incl. certificate(s)]**
 <Subject>
 <NameID>https://www.google.com/accounts/08/id? id = xxxxx
 <SubjectConfirmation Method=“**Bearer**”>
 <Conditions NotBefore=“...” NotAfter=“...” >
 <AudienceRestriction><Audience>https://www.rp.ciws:8443
 <AttributeStatement>
 <Attribute Name = “emailaddress”>
 <AttributeValue>alice4demos@gmail.com
 <Attribute Name = “name”>
 <AttributeValue>Alice Demos
 <Attribute Name = “identityprovider”>
 <AttributeValue>Google


Federation



Relations



Relations - keys



Relations - endpoints



Metadata – Identity Provider

[<https://demos-ciws.accesscontrol.appfabriclabs.com/FederationMetadata/2007-06/FederationMetadata.xml>]

<EntityDescriptor>

<Signature> [XML DSIG signature]

<**RoleDescriptor** type="**SecurityTokenService**">

<KeyDescriptor use="signing"><KeyInfo> **[X509Certificate]** [copy to file]

<ClaimTypesOffered>...

<SecurityTokenServiceEndpoint>

<EndpointReference> [WS-Addressing endpoint reference]

<SecurityTokenServiceEndpoint>

<EndpointReference> [WS-Addressing endpoint reference]

<PassiveRequestorEndpoint>

<EndpointReference><Address>

<https://demos-ciws.accesscontrol.appfabriclabs.com/v2/wsfederation>

<RoleDescriptor type="ApplicationServiceType">

(...)

Metadata – www.rp.ciws

<EntityDescriptor>

<RoleDescriptor type="ApplicationServiceType">

<ClaimTypesRequested>

<ClaimType Uri=".../name" Optional="true" />

<ClaimType Uri=".../role" Optional="true" />

<TargetScopes>

<EndpointReference><Address>https://www.rp.ciws:8443/

<PassiveRequestorEndpoint>


<EndpointReference><Address>https://www.rp.ciws:8443/

WINDOWS IDENTITY FOUNDATION

WIF

- Class model for identity representation
- Protocol and token handling
- Claims consumption pipeline
 - Token validation
 - Identity transformation
 - Authorization decision
- Claims issuance pipeline

Claims object model



Claim types

```
public static class ClaimTypes {  
    public const string AuthenticationInstant = "...";  
    public const string AuthenticationMethod = "...";  
    public const string DateOfBirth = "...";  
    public const string Dns = "...";  
    public const string Email = "...";  
    public const string Gender = "...";  
    public const string GivenName = "...";  
    public const string GroupSid = "...";  
    public const string HomePhone = "...";  
    public const string Name = "...";  
    public const string PostalCode = "...";  
    public const string PPID = "...";  
    public const string Role = "...";  
    public const string Rsa = "...";  
    public const string StreetAddress = "...";  
    public const string Surname = "...";  
    public const string WindowsAccountName = "...";  
    public const string X500DistinguishedName = "...";  
    (...)  
}
```

Value types

```
public static class ClaimValueTypes
```

```
{
```

```
    public const string Base64Binary = "http://www.w3.org/2001/XMLSchema#base64Binary";  
    public const string Boolean = "http://www.w3.org/2001/XMLSchema#boolean";  
    public const string Date = "http://www.w3.org/2001/XMLSchema#date";  
    public const string Datetime = "http://www.w3.org/2001/XMLSchema#dateTime";  
    public const string DaytimeDuration = ".../WD-xquery-operators-20020816#dayTimeDuration";  
    public const string Double = "http://www.w3.org/2001/XMLSchema#double";  
    public const string HexBinary = "http://www.w3.org/2001/XMLSchema#hexBinary";  
    public const string Integer = "http://www.w3.org/2001/XMLSchema#integer";  
    public const string KeyInfo = "http://www.w3.org/2000/09/xmldsig#KeyInfo";  
    public const string Rfc822Name = "urn:oasis:names:tc:xacml:1.0:data-type:rfc822Name";  
    public const string RsaKeyValue = "http://www.w3.org/2000/09/xmldsig#RSAKeyValue";  
    public const string String = "http://www.w3.org/2001/XMLSchema#string";  
    public const string Time = "http://www.w3.org/2001/XMLSchema#time";  
    public const string X500Name = "urn:oasis:names:tc:xacml:1.0:data-type:x500Name";  
    public const string YearMonthDuration = "http://...20020816#yearMonthDuration";
```


```
}
```

Protocol Handling


- ASP.NET modules
 - WSFederationAuthenticationModule (FAM)
 - SessionAuthenticationModule (SAM)

```
<system.webServer>  
  <modules runAllManagedModulesForAllRequests="true">  
    <add name="..." type="WSFederationAuthenticationModule, ..." />  
    <add name="..." type="SessionAuthenticationModule, ..." />  
  </modules>  
</system.webServer>
```


WS-Federation Authn Module (FAM)




ASP.NET Integration



ASP.NET Integration

- Using a *legacy* authentication mechanism
 - e.g. Forms authentication, MVC filters



Configuration (web.config)

```
<microsoft.identityModel>
```

```
  <service>
```

```
    <audienceUri><add value="https://www.rp.ciws:8443/" />
```

```
    <federatedAuthentication>
```

```
      <wsFederation passiveRedirectEnabled="true"
```

```
        issuer="https://demos-ciws.accesscontrol.appfabrilabs.com/v2/ws federation"
```

```
        realm="https://www.rp.ciws:8443" requireHttps="true" />
```

```
      <cookieHandler requireSsl="true" />
```

```
    <applicationService><claimTypeRequired>
```

```
      <claimType type=".../name" optional="true" />
```

```
      <claimType type=".../role" optional="true" />
```

```
      <!--<claimType type=".../nameidentifier" optional="true" />-->
```

```
      <!--<claimType type=".../identityprovider" optional="true" />-->
```

```
    <issuerNameRegistry type="...ConfigurationBasedIssuerNameRegistry>
```

```
    <trustedIssuers>
```

```
      <add thumbprint="67F6E7E72A93776D3AEA5EB73537077626B90FDF"
```

```
        name="https://demos-ciws.accesscontrol.appfabrilabs.com/" />
```

```
    <certificateValidation certificateValidationMode="None" />
```

Configuration (web.config)


- Additional changes introduced by fedutil
 - `<authorization><deny users="?" />`
 - `<authentication mode="None" />`
 - Allow users="*" to path="FederationMetadata"

Access Control Service (ACS)

- Part of Azure AppFabric
- Version 1 in production, version 2 in “labs”
- SaaS – Software as a Service
 - Service namespace \approx tenant
- Claims transformer



ACS configuration




- Identity Providers
 - Relation with *upstream* IdPs
- Relying Parties
 - Relation with downstream RPs
- Rule groups
 - Claims transformation rules
- Certificates and keys
- Service identities
 - Direct identities and credentials
- Application integration
 - Addresses


Hands-On-Lab 2

- Create a new ACS tenant
- Configure a new RP
- Activate support for Google IdP
- Define some rules
- Change relying party to use this new tenant
- Start at <https://portal.appfabriclabs.com/>


WIF Consumer Pipeline




WIF Consumer Pipeline




WIF Consumer Pipeline



WIF Consumer Pipeline



WIF Consumer Pipeline



```
<issuerNameRegistry
  type="...ConfigurationBasedIssuerNameRegistry...">
  <trustedIssuers>

    <add name="demos-ciws" thumbprint="a1...74"/>
    <add name="other-issuer" thumbprint="72...8e"/>


  </trustedIssuers>
</issuerNameRegistry>
```

WIF Consumer Pipeline


```
public override IClaimsPrincipal
Authenticate(string resourceName, IClaimsPrincipal incomingPrincipal)
{
    if(incomingPrincipal.Identities[0].Claims.Any(c =>
        c.ClaimType.Equals(ClaimTypes.Email) &&
        c.Value.Equals("alice4demos@gmail.com")) &&
        incomingPrincipal.Identities[0].Claims.Any(c =>
            c.ClaimType.Equals("http://.../accesscontrolservice/.../identityprovider") &&
            c.Value.Equals("Google")))
    {
        incomingPrincipal.Identities[0].Claims.Add(
            new Claim(ClaimTypes.Role, "http://www.cc.isel.ipl.pt/roles/member"));
    }
    return incomingPrincipal;
}
```

Host (e.g. ASP.NET, WCF)


WIF Consumer Pipeline



WIF Consumer Pipeline




WIF Consumer Pipeline (ASP.NET)



WSFAM

FAM: properties



FAM: Public methods

The screenshot displays the 'WSFederationAuthenticationModule' class in Visual Studio. The class is identified as a 'Class' that inherits from 'HttpModuleBase'. The 'Methods' section is expanded, showing a list of public methods. Several methods are underlined in red, indicating they are the focus of the presentation. The methods listed are: CanReadSignInResponse (+ 1 overload), CreateSignInRequest, FederatedSignOut, GetFederationPassiveSignOutUrl, GetSecurityToken (+ 1 overload), GetSignInResponseMessage, GetXmlTokenFromMessage (+ 1 overload), IsSignInResponse, RedirectToIdentityProvider, SetPrincipalAndWriteSessionToken, SignOut, VerifyProperties, and WSFederationAuthenticationModule. The 'Events' section is also visible but collapsed.


WSFederationAuthenticationModule
Class
↳ HttpModuleBase

Methods

- CanReadSignInResponse (+ 1 overload)
- CreateSignInRequest
- FederatedSignOut
- GetFederationPassiveSignOutUrl
- GetSecurityToken (+ 1 overload)
- GetSignInResponseMessage
- GetXmlTokenFromMessage (+ 1 overload)
- IsSignInResponse
- RedirectToIdentityProvider
- SetPrincipalAndWriteSessionToken
- SignOut
- VerifyProperties
- WSFederationAuthenticationModule


Events


FAM: events


WSFederationAuthenticationModule


Class


→ [HttpModuleBase](#)





 Properties


 Methods


 Events


 [AuthorizationFailed](#)


 [RedirectingToIdentityProvider](#)


 [SecurityTokenReceived](#)


 [SecurityTokenValidated](#)


 [SessionSecurityTokenCreated](#)

 SignedIn

 SignedOut

 SignInError

 SigningOut


 SignOutError

ASP.NET SESSION MANAGEMENT

Session management

- The sign in response contains the issued token
 - The next HTTP requests don't
 - Preserve authentication info between requests
- Cookies and session tokens
- **SessionAuthenticationModule**
 - Handles **OnAuthenticateRequest**
 - Tries to read session token from cookie
 - Sets request identity from token claims
 - Updates session token and cookies




Session management



Network Load Balancing (NLB)

- **ProtectDataCookieTransform** used by default
 - Data Protection API – machine/account bound
 - Not suitable for NLB environment
- Solution
 - Use the RSA based cookie transforms
 - Encryption and signature
 - Use the same key pair in all machines
 - Typical in HTTPS scenarios

Federation messages



Controls

- FederatedPassiveSignIn
- FederatedPassiveSignInStatus

WIF CONFIGURATION

WIF configuration

- Host independent configuration
 - Token processing
 - Authorization manager
 - **<service>** element
 - **ServiceConfiguration** type
- ASP.NET specific configuration
 - FAM and SAM modules; cookie handling
 - **<federatedAuthentication>** element
 - **FederatedAuthentication** static class

Service Configuration

- Token processing
 - Audience restrictions
 - Security token handlers
- Issuer naming
- Certificate validation
 - None | Peer | Chain | Custom
 - Revocation mode
- Certificate resolution
 - External
 - Service
- Managers (generic pipeline)
 - Authentication
 - Authorization

Service configuration

- XML

```
<microsoft.identityModel>
```

```
  <service>
```

```
    <federatedAuthentication>
```

```
      [default configuration]
```


```
    <service name = "configname">
```

```
      [alternate configuration]
```


- Code

- **ServiceConfiguration** ctor(**configname**)
- **FederatedAuthentication** static methods

FederatedAuthentication



ServiceConfiguration class



Token handlers

- XML

```
<securityTokenHandlers>
```

```
  <securityTokenHandlerConfiguration> ...
```


```
<securityTokenHandlers name = "configname">
```

```
  <securityTokenHandlerConfiguration> ...
```

- Code

- Named collections – handler collection manager

SecurityTokenHandlerConfiguration



Configuration extensibility


- Inner XML passed as XmlNodeList on the ctor
- Elements
 - IssuerNameRegistry
 - ClaimsAuthorizationManager
 - SecurityTokenHandler
- Example

```
<issuerNameRegistry type="ConfigurationBasedIssuerNameRegistry, ...">  
  <trustedIssuers>  
    <add name="issuename" thumbprint="certificate hash" />  
  </trustedIssuers>  
</issuerNameRegistry>
```

Hands-On-Lab 3

- Explore WIF and ASP.NET extensibility
 - NLB scenarios and session management
 - Explicit authentication
 - ASP.NET WebForms and WIF controls
 - ASP.NET MVC account controller
 - Home realm selection
 - Authentication and Authorization Managers

Azure project



Definition and configuration

- Definition file (.csdef)
 - Static
 - Endpoints
 - Settings names
 - ...
- Configuration file (.cscfg)
 - Dynamic
 - Settings values
 - Instance count
 - ...

Azure Project

- Build output
 - Package file (.cspkg)
 - Configuration file (.cscfg)
- Package file
 - Compressed archive
 - Service model
 - Project outputs

Azure and WIF

- Certificate management
- HTTPS endpoints
- WIF assemblies
- Host names and environment differences
- Load balancing

Certificate management (1)

- Certificates and private keys upload
 - Via the management portal only
 - Administrator task (private key management)
 - Service scoped
 - PFX (PKCS #12) format
 - Certificate and private key
 - Certificate only

Certificate management (2)

- Role definition

```
<Certificates>
```

```
  <Certificate name="rp-ciws.cloudapp.net"  
    storeLocation="LocalMachine" storeName="My" />
```

```
<Endpoints>
```

```
  <InputEndpoint name="..." protocol="https" port="433"  
    certificate="rp-ciws.cloudapp.net" />
```

- Role configuration

```
<Certificate name="rp-ciws.cloudapp.net"  
  thumbprint="78...CC" />
```

→ Matches certificate uploaded by admin

WIF assemblies

- **WIF is not installed** on the Azure platform
- Solutions
 - Upload Microsoft.IdentityModel.dll
 - Copy Local = “true”
 - Some limitations
 - Use a role startup task
 - Installs WIF runtime on role startup

Role startup

- Role definition

```
<WebRole name="...">
```

```
  <Startup>
```

```
    <Task commandLine="\\Startup\SetupWifRuntime.cmd"  
      executionContext="elevated" taskType="simple" />
```

- Copy to output directory

- SetupWifRuntime.bat

```
sc config wuauserv start= demand
```

```
wusa.exe "%~dp0Windows6.1-KB974405-x64.msu" /quiet /norestart
```

```
sc config wuauserv start= disabled
```


- Windows6.1-KB974405-x64.msu (windows update)

Host names

- Three different environments
 - Local machine - Developer Fabric
 - Staging deploys – random host names
 - Production deploys – chosen host name
 - E.g. **rp-ciws.cloudapp.net**
- Federation with identity provider
 - Tied to a host name

Load balancing

- Role instances are behind a NLB
 - No “sticky sessions”
- Use custom session management
 - Cookie protection using RSA key
 - Custom session token cache



Hands-On-Lab 4

- Claims based relying party on Azure
 - Create Azure project
 - Add web role based on existing project
 - Configure certificates
 - Test on local machine – development fabric
 - Create hosted service
 - Upload certificates
 - Publish service
 - Test on Azure

WCF

- Same
 - WIF claims class model
 - WIF processing pipeline (token handlers, issuer registries, ...)
 - SAML token format
- Different
 - Token transport protocols (WS-Trust, not WS-Federation)
 - Metadata (WSDL, WS-Policy and WS-SecurityPolicy)
 - Token binding (WS-Security and holder-of-key)


Protocols – passive scenario

- User-agent follows HTTP and HTML+script specs.
 - HTTP redirections and auto-post forms
- No user-agent intervention on exchanged messages
 - No message protection (only transport protection)
 - No proof-of-possession
- Embedded interactions with UI
 - Custom authentication and identity disclosure interactions


Protocols – active scenario

- Client has the initiative to obtain tokens
 - Guided by code, configuration or policy
- Client processes the messages
 - Message protection (signature and encryption)
 - Message authentication (token proof-of-possession)


Passive




Active



Active






WS-*

- **WS-Security**
 - SOAP message protection XML-Signature/Encryption
 - SOAP message authentication using *binded* **security tokens**
- **WS-Trust**
 - Request-reply protocol for **requesting issued tokens**
 - Security Token Service (STS)
- **WS-SecurityPolicy**
 - Metadata containing the **token requirements** (issuer, claims) - **policies**
- **WS-MetadataExchange**
 - Protocol for obtaining the **policies**

WS-Security



WS-Trust messages

- **RequestSecurityToken (RST)** message
 - Requestor identity claims (security token)
 - Requested token characteristics:
 - Token type, claims, key type
 - Token consumer (**AppliesTo**)
- **RequestedSecurityTokenResponse (RSTR)** message
 - Issued Token
 - Proof of Possession information

Proof of Possession

- Symmetric key
 - Derived by both the requestor and the STS
 - **Encrypted to token consumer – STS must know the token consumer**
- Public key
 - Sent in the RST
 - Present in the issued token

WCF concepts


- Endpoint
 - Contract
 - **Binding**
 - Address
- **Behaviors**
 - Service scope
 - Endpoint scope
 - Contract scope

WCF and security

- Bindings - defines the security “type”
 - Publicized in the metadata
 - Token type and issuer, required claims, algorithms
 - Scoped to an endpoint
- Credentials – defines the security “values”
 - Usernames and passwords, certificates, certificate validation
 - Scope
 - **ServiceCredentials (IServiceBehavior)**
 - **ClientCredentials (IEndpointBehavior)**


Federation bindings

- Federation bindings
 - Token request done automatically by the binding
 - Token request uses inner binding (issuer binding)



Simple scenario

- Using ACS as a claims provider
 - RP accepts issued token
 - Client uses username+password to authn with ACS



Simple scenario - Service

- Define binding and add endpoint

```
var binding = new WS2007FederationHttpBinding(  
    WSFederationHttpSecurityMode.Message);  
binding.Security.Message.IssuedKeyType = SecurityKeyType.SymmetricKey;  
binding.Security.Message.IssuedTokenType =  
    SecurityTokenTypes.OasisWssSaml2TokenProfile11;  
host.AddServiceEndpoint(typeof(...), binding, "http://soap.rp.ciws");
```


Simple scenario - Service

- Define service certificate
 - Host service credentials

```
host.Credentials.ServiceCertificate.Certificate =  
    X509StoreExt.GetCertificateFromStoreBySubjectName(  
        StoreName.My,  
        StoreLocation.LocalMachine,  
        "soap.rp.ciws");
```

Simple scenario - Service

- Configure WIF

```
var wifconfig = new ServiceConfiguration();  
wifconfig.CertificateValidationMode =  
    X509CertificateValidationMode.None;  
wifconfig.AudienceRestriction.AllowedAudienceUris.Add(  
    new Uri("http://soap(rp.ciws)"));  
var issuerReg = wifconfig.IssuerNameRegistry as  
    ConfigurationBasedIssuerNameRegistry;  
issuerReg.AddTrustedIssuer("67...DF",  
    "https://demos-ciws.accesscontrol.appfabriclabs.com");  
  
FederatedServiceCredentials.ConfigureServiceHost(host, wifconfig);
```

Simple scenario - Client

```
using (var cf = new ChannelFactory<...>(GetBinding2, address)) {  
    cf.Credentials.ServiceCertificate.DefaultCertificate =  
        X509StoreExt.GetCertificateFromStoreBySubjectName(  
            StoreName.My, StoreLocation.LocalMachine, "soap.rp.ciws");  
  
    cf.Credentials.ServiceCertificate.Authentication.RevocationMode =  
        X509RevocationMode.NoCheck;  
  
    cf.Credentials.UserName.UserName = "Alice";  
    cf.Credentials.UserName.Password = "...";  
    ...  
}
```

Simple scenario - Client

```
private static Binding GetBinding1(){  
    var homeBinding = new  
        WS2007HttpBinding(SecurityMode.TransportWithMessageCredential);  
    homeBinding.Security.Message.ClientCredentialType =  
        MessageCredentialType.UserName;  
    homeBinding.Security.Message.NegotiateServiceCredential = true;  
    homeBinding.Security.Message.EstablishSecurityContext = false;  
  
    var rpBinding = new  
        WS2007FederationHttpBinding(WSFederationHttpSecurityMode.Message);  
    rpBinding.Security.Message.IssuedKeyType = SecurityKeyType.SymmetricKey;  
    rpBinding.Security.Message.IssuedTokenType =  
        SecurityTokenTypes.OasisWssSaml2TokenProfile11;  
  
    rpBinding.Security.Message.IssuerAddress = new EndpointAddress(  
        "https://demos-ciws.accesscontrol.appfabriclabs.com/v2/wstrust/13/username");  
    rpBinding.Security.Message.IssuerBinding = homeBinding;  
    return rpBinding;  
}
```


Issuer characterization

- Consumer defines issuer metadata address and endpoint address
 - Client can use **svcutil** tool or **MetadataResolver** class to obtain service endpoint
- Consumer defines issuer metadata address only
 - Client can use **svcutil** tool or **MetadataResolver** class to obtain service endpoint.
 - The first issuer compatible endpoint will be user; can be changed in config
- Consumer doesn't define any issuer address
 - Client must configure issuer information
 - Binding's issuer address and binding
 - Credentials' local issuer address and binding


WCF and WIF Integration

- Bindings
 - No changes, same model
 - E.g. WS2007FederationHttpBinding, ...
- **ServiceCredentials**
 - Replaced by the WIF pipelining
 - Uses WCF extensibility points
 - Not compatible with WCF native model
 - Some **ServiceCredentials** settings don't work
 - WIF claims class model and authn/authz managers


WS2007FederationHttpBinding



ClientCredentials



ServiceCredentials



Hands-on-Lab 5

- Create an IIS based WCF service
- Create a console client
- Use fedutil to federate with ACS
- Update service reference
- Reconfigure client settings