Kiln

▎ Kiln » ▦ TortoiseHg » ▌ Shell Extension   ▌ **Mercurial ▼**

| **History** | ▌ Files | ▌▌ Related | Clone URL: `https://developers.kilnhg.com/Code/Kiln/Torto` |

Pushed to <u>one repository</u> · │ <u>View In Graph</u>   Contained in **tip** ✎

RunDialog: don't add backslash to end of directory if it already has one ...

by **David Golub**   Changeset <u>3ed4b665ddf9...</u>
Aug 10 11 at 2:59 PM   Parent <u>382bee2ee7ce...</u>

SHOWING DIFF FROM PARENT <u>382bee2ee7ce</u>   <u>Diff from another changeset...</u>   Changes to <u>one file</u> · <u>Browse files at 3ed4b665ddf9</u>

▌ <u>src/RunDialog.cpp</u>   ⚙ Stacked ▼   <u>Show Entire File</u>   │ Change 1 of 2 ▎

```
@@ -31,14 +31,15 @@
31    31            ATLTRACE(_T("RunDialog: THG root is empty\n"));
32    32            return;
33    33        }
34    -       CString strHgCmd = strDir + _T("\\thgw.exe");
      34   +       if (!EndsWith(strDir, _T("\\"))) strDir += _T("\\");
      35   +       CString strHgCmd = strDir + _T("thgw.exe");
35    36
36    37        if (!::PathFileExists(strHgCmd))
37    38        {
38    -           strHgCmd = strDir + _T("\\hgtk.exe");
      39   +           strHgCmd = strDir + _T("hgtk.exe");
39    40            if (!::PathFileExists(strHgCmd))
40    41            {
41    -               strHgCmd = strDir + _T("\\thg.cmd");
      42   +               strHgCmd = strDir + _T("thg.cmd");
42    43            }
43    44        }
44    45
@@ -64,7 +65,7 @@
64    65        {
65    66            if (CTHgStatus::Remove(strCwd) != 0)
66    67            {
67    -               CString strPath = strDir + _T("\\TortoiseHgOverlayServer.exe");
      68   +               CString strPath = strDir + _T("TortoiseHgOverlayServer.exe");
68    69                LaunchCommand(Quote(strPath), strDir);
69    70            }
70    71        return;
```